

, 10 1

1. : C450 Scratch Resistant Rapid Repair Clear C450 Uses in Coatings - Clearcoat : Valspar b.v. (Sherwin-Williams) valspar Zuiveringweg 89 8243 PE Lelystad The Netherlands tel: +31 (0)320 292200 fax: +31 (0)320 292201 26-14, 705 ( tel: 031-425-7881 fax: 031-425-7882 : ( ) 354-42, 3 tel: 054-971-7757 fax: 054-971-7758 : 031 - 425 - 7881 +31 (0)320 292200 -) ( 2. ) - 3 : 29.6% : 42.3%

/ :2017 8 7 :1 1/13

```
C450 Scratch Resistant Rapid Repair Clear
2.
                                                   : > 8
                                                                                  EN 374
                              PVA)
                                             >= 0.7 mm; < 1
                                                                          ):
                                                           ; EN374:
                                                                                - NBR (> = 0.35 \text{ mm}).
                                                                가
                                                                                                 가
                                                  가
                                                   가
                                                                                     . 가
                                      가
                                                                        가
3.
<u>CAS</u>
 CAS
EU
                            : 502116
                                                                   CAS
                                                                                       %
                                         DIMETHYL KETONE
                                                                   67-64-1
                                                                                       10 - 25
                                         BUTYL ACETATE
                                                                   123-86-4
                                                                                       10 - 25
2-
                                         METHYL N-AMYL KETONE
                                                                   110-43-0
                                                                                       10 - 25
                                         METHYL ISOBUTYL
                                                                   108-10-1
                                                                                       1 - 3
                                         KETONE
                                         SILICONE SURFACTANT
                                                                   68938-54-5
                                                                                       1 - 3
4-chloro-a,a,a, trifluorotoluene
                                                                   98-56-6
                                         trifluorotoluene
                                                                                       10 - 16
```

· 가 8 .

가

가

/ : 2017 8 7 : :2019 2 8 :1 2/13

```
4.
가.
                                           가
                          ÷
                                                                                     10
                                      가
                                                                                            (
                            hume)
                                                                                         가
                                          가
                                                                           (recovery position)
                                                                   48
                                                                                         가
                                                                                  가
                                                                   가
                                                                                    가
                                        가
                                                                     (
                                                                         )
                                   (recovery position)
                                                                                           48
                                            가
                            hume)
                                                                                    가
                    . (11 )
5.
                                              가 ,
                                                                     가가
                                              .
가
                                                                                       가
```

/ :2017 8 7 :1 3/13

```
C450 Scratch Resistant Rapid Repair Clear
5.
                                                                                      가
                               SCBA)
                                   가
6.
                                                     가
                                 가
                                                    (13
                                                                   가
                                      13
7.
                                                                (8
                                                                        ).
                                                                                                       가
                                                                가
                                              가
                                                                                             가
                                                          .
가
                                                  , 가
                                                      가
8
                                             가
```

/ : 2017 8 7 : :2019 2 8 :1 4/13

```
C450 Scratch Resistant Rapid Repair Clear
7.
                                                                               가
                                               가
                                                          (10
                                                                       )
                                          ,
가
8.
                                                                        Ministry of Labor (, 8/2013).
                                                                         STEL: 1782 mg/m<sup>3</sup> 15 .
                                                                         STEL: 750 ppm 15 .
                                                                         TWA: 1188 mg/m<sup>3</sup> 8
                                                                         TWA: 500 ppm 8
                                                                                              , 8/2013).
                                                                        Ministry of Labor (
                                                                         STEL: 950 mg/m<sup>3</sup> 15 .
                                                                         STEL: 200 ppm 15 .
                                                                         TWA: 710 mg/m<sup>3</sup> 8
                                                                         TWA: 150 ppm 8
    2-
                                                                        Ministry of Labor (
                                                                                               , 8/2013).
                                                                        TWA: 235 mg/m<sup>3</sup> 8
                                                                         TWA: 50 ppm 8
                                                                        Ministry of Labor (
                                                                                              , 8/2013).
                                                                         STEL: 300 mg/m<sup>3</sup> 15
                                                                         STEL: 75 ppm 15
                                                                         TWA: 205 mg/m<sup>3</sup> 8
                                                                         TWA: 50 ppm 8
                                     가
                                                                                                           가
                                                                                                    가
                                                                       가
                                         (fume scrubbers),
                                        가
                                                    가
                                                                    : EN 405:2001 + A1:2009
                                                                                                               A)
                                                   FFA2P3 R D
                                           가
                                                        가
                                                                         ,가,
                                                                                                               가
                                                                                                가
```

/ : 2017 8 7 : :2019 2 8 :1 5/13

```
8.
                                   가
                                                                              ,
가
                                                EN 374
                                    ):
(
                                                                     (PVA)
                                                                                    >= 0.7 mm
                                             ):
                                                       ; EN374 :
                                                                         - NBR (> = 0.35 \text{ mm}).
                                               가
                                                                  가
9.
 . pH
                                 (>132.8)
                            >56
                           : Closed cup: -6.5 (20.3 )
                            0.958
```

/ : 2017 8 7 : :2019 2 8 : :1 6/13

10.

:

가. 가

) 가 가

가:

11.

가. 가

(CNS)

(CNS)

/				
	LC50	(rat)	76 mg/l	4
	LD50	, ,	>15800 mg/kg	-
	LD50	(rat)	5800 mg/kg	-
	LC50	(rat)	>21.1 mg/l	4
	LD50	, ,	>14112 mg/kg	-
	LD50	(rat)	10760 mg/kg	-
2-	LC50	(rat)	>16.7 mg/l	4
	LD50	(rat)	>2000 mg/kg	-
	LD50	(rat)	1600 mg/kg	-
	LC50	(rat)	8.2 - 16.4 mg/l	4
	LD50	, ,	>2000 mg/kg	-
	LD50	(rat)	2080 mg/kg	-
Siloxanes and Silicones,	LC50	(rat)	1.08 mg/l	4
		(,	] 3,1	

7/13 : 2017 8 7 : 1

Scratch Resistant Rapid Repair Cl	ear						
di-Me, 3-hydroxypropyl Me, ethers with polyethylene glycol mono- Me ether	LD50		(rat)		>200	0 mg/kg	-
	LD30		(lat)		/200	o mg/kg	
				1			
/						40000	
	-			-		186300 parts per million 10	-
	-			-		microliters 24 20	-
	-			-		milligrams 20 milligrams	-
	-			-		24 500 milligrams 395	
2-	-			-		milligrams 24 14 milligrams	-
	-			-		24 100 microliters	
	-			-		40 milligrams 24 500 milligrams	- )
· .							
(1	)						
2-		3 3 3 3					
· .	_)					·	
/	: 2017 8 7			:2019			:1

11.

: : :

787.2 mg/kg ( ) 6.84 mg/l

## 12.

가.

			-
/			
	EC50 8800 mg/l	- Daphnia	48
	Ŭ	pulex	
	LC50 5540 mg/l	- Oncorhynchus	96
		mykiss	
	NOEC 530 mg/l	(藻類) - Microcystis	8
		aeruginosa	
	EC50 647.7 mg/l	(藻類) - Desmodesmus	72
	, and the second	subspicatus	
	EC50 44 mg/l	·	48
	LC50 32 mg/l	- Artemia salina	48
	LC50 18 mg/l	- Pimephales	96
		promelas	
	NOEC 200 mg/l	(藻類)	72
	NOEC 23 mg/l	- Daphnia	21
		magna	
2-	LC50 131000 - 137000 μg/l	- Pimephales	96
		promelas	
	EC50 400 mg/l	(藻類)	96
	EC50 >200 mg/l	- Daphnia	48
		magna	
	LC50 >179 mg/l	- Danio rerio	96
Siloxanes and Silicones, di	EC50 58 mg/l	- Daphnia	48
-Me, 3-hydroxypropyl Me,		magna	
ethers with polyethylene			
glycol mono-Me ether			
	LC50 7 mg/l		96

/ : 2017 8 7 : :2019 2 8 :1 9/13

150 Scratch Resistant I	парта перат отсат					
2.						
/	OECD 301D Ready Biodegradability - Closed Bottle	>80 % - 5		-		-
2-	Test -	69 % -	- 28	-		-
/				•		
2-	- - -		-			
1	LogPow		BCF			
2-	-0.23 2.3 2.26 1.9		- - -			
	(K <sub>oc</sub> ) : .					
3.			가		, 7L	가 .
	:		가 가 가	·	, 가	가 ·
	:	7	가			
	:	7	가 ŀ .			가 가 ',
	: : 가 :	7	가 가		가	가 ,
	: : 가	7 UN1263	가 가 · ·	UN1	가	,
4.	: : 가		가 가 · ·	UN1	가 <sup>L</sup> 263	가 ,
4. +.	: 가 : 가 : :	UN1263	가 가 · ·		가 <sup>L</sup> 263	가 ,

:2019

2 8

: 1

10/13

: 2017 8 7

C450 Scratch Resistant Rapid Repair Clear 14. Ш Ш No. No. Emergency schedules (EmS) F-E, \_S-E\_ 가 Passenger and Cargo AircraftQuantity limitation: 5 163 Packaging instructions: 353 Special provisions 163 Cargo Aircraft OnlyQuantity limitation: 60 L Packaging instructions: 364 <u>Limited Quantities -</u> Passenger AircraftQuantity limitation: 1 L Packaging instructions: Y Special provisions A3, A72 가 15. 37 38 2 2n-; nn-:2017 8 7 : 1 11/13

:2019

2 8

```
C450 Scratch Resistant Rapid Repair Clear
```

15.

```
16.
가.
                          : 2017 8 7
                          : 1
  Key to abbreviations
                          : ATE =
                            BCF =
                            GHS =
                            IATA =
                            IBC =
                            IMDG =
                            LogPow = /
                            MARPOL 73/78 = 1973
                                                                                          1978
                                   ("Marpol" =
                            UN =
```

/ : 2017 8 7 : :2019 2 8 :1 12/13

가 . ,

. 가

/ : 2017 8 7 : :2019 2 8 :1 13/13